



PRODUCT FEATURES

- *Ideal For Street, High Bay, Low Bay Lighting
- *Up to 223 lm/W LED Module Efficiency
- *3535 Package High Performance LEDs
- *Wide CCT Ranging from 2200K – 6500K
- *Long Life-Time: > 100.000 Hours L70B10 @105°C
- *Minimum Colour Tolerance: 3MacAdam (3SDCM)
- *Compatible with Ledil STRADA-IP-2x6 and HB-IP-2x6 Families



Product Code	CCT K	Current mA	Flux tc 25°C lm	Flux tc 85°C lm	Power tc 85°C W	Efficacy tc 25°C lm/W	Efficacy tc 85°C lm/W	Vmin. Tc 85°C	Vmax. Tc 25°C
PALS00001-1P12S-22-3535	2200	350	2120	1938	11,0	185,9	176,4	31,44	36,36
		700	3904	3568	23,0	163,6	155		
		1050	5441	4971	35,8	146,7	138,7		
		1400	6697	6117	49,2	131,6	124,3		
PALS00001-1P12S-27-3535	2700	350	2120	1938	11,0	185,9	176,4		
		700	3904	3568	23,0	163,6	155		
		1050	5441	4971	35,8	146,7	138,7		
		1400	6697	6117	49,2	131,6	124,3		
PALS00001-1P12S-30-3535	3000	350	2544	2325	11,0	223	196,3		
		700	4685	4281	23,0	196,3	186		
		1050	6529	5965	35,8	176	166,4		
		1400	8037	7340	49,2	157,9	149,2		
PALS00001-1P12S-40-3535	4000	350	2544	2325	11,0	223	211,7		
		700	4685	4281	23,0	196,3	186		
		1050	6529	5965	35,8	176	166,4		
		1400	8037	7340	49,2	157,9	149,2		
PALS00001-1P12S-50-3535	5000	350	2544	2325	11,0	223	211,7		
		700	4685	4281	23,0	196,3	186		
		1050	6529	5965	35,8	176	166,4		
		1400	8037	7340	49,2	157,9	149,2		
PALS00001-1P12S-65-3535	6500	350	2403	2196	11,0	210,6	199,9		
		700	4424	4043	23,0	185,4	175,6		
		1050	6166	5633	35,8	166,2	157,2		
		1400	7590	6932	49,2	149,2	140,9		