



### PRODUCT FEATURES

- \*Ideal For Street, High Bay, Low Bay Lighting
- \*Up to 223 lm/W LED Module Efficiency
- \*3535 Package High Performance LEDs
- \*Wide CCT Ranging from 2200K – 6500K
- \*Long Life-Time: >100.000 Hours L70B10 @105°C
- \*Minimum Colour Tolerance: 3MacAdam (3SDCM)
- \*Compatible with Ledil Strada-2x2 and HB-2x2 Families



Product Code	CCT K	Current mA	Flux tc 25°C lm	Flux tc 85°C lm	Power tc 85°C W	Efficacy tc 25°C lm/W	Efficacy tc 85°C lm/W	Vmin. Tc 85°C	Vmax. Tc 25°C
PALS00011-1P16S-22-3535	2200	350	2827	2584	14,6	185,9	176,4	41,92	48.48
		700	5205	4757	30,7	163,6	155		
		1050	7254	6627	47,8	146,7	138,7		
		1400	8930	8156	65,6	131,6	124,3		
PALS00011-1P16S-27-3535	2700	350	2827	2584	14,6	185,9	176,4		
		700	5205	4757	30,7	163,6	155		
		1050	7254	6627	47,8	146,7	138,7		
		1400	8930	8156	65,6	131,6	124,3		
PALS00011-1P16S-30-3535	3000	350	3392	3101	14,6	223	211,7		
		700	6246	5708	30,7	196,3	186		
		1050	8705	7953	47,8	176	166,4		
		1400	8037	7340	49,2	157,9	149,2		
PALS00011-1P16S-40-3535	4000	350	3392	3101	14,6	223	211,7		
		700	6246	5708	30,7	196,3	186		
		1050	8705	7953	47,8	176	166,4		
		1400	10716	9787	65,6	157,9	149,2		
PALS00011-1P16S-50-3535	5000	350	3392	3101	14,6	223	211,7		
		700	6246	5708	30,7	196,3	186		
		1050	8705	7953	47,8	186	176		
		1400	10716	9787	149,2	157,9	149,2		
PALS00011-1P16S-65-3535	6500	350	3204	2928	14,6	210,6	199,9		
		700	5899	5391	30,7	185,4	175,6		
		1050	8222	7511	47,8	166,2	157,2		
		1400	10120	9243	65,6	149,2	140,9		