



PRODUCT FEATURES

- *Ideal For Street, High Bay, Low Bay Lighting
- *Up to 205 lm/W LED Module Efficiency
- *5050 Package High Performance LEDs
- *Wide CCT Ranging from 2200K – 6500K
- *Long Life-Time: >100.000 Hours L70B10 @105°C
- *Minimum Colour Tolerance: 3MacAdam (3SDCM)
- *Compatible with Ledil Strada-2x2 and HB-2x2 Families



Product Code	CCT K	Current mA	Flux tc 25°C lm	Flux tc 85°C lm	Power tc 85°C W	Efficacy tc 25°C lm/W	Efficacy tc 85°C lm/W	Vmin. Tc 85°C	Vmax. Tc 25°C
PALS00012-2P8S-22-5050	2200	700	5123	4629	31,3	161,4	147,9	44,72	48,32
		1050	7325	6615	48,5	148,9	136,3		
		1400	9266	8363	66,7	137	125,3		
PALS00012-2P8S-27-5050	2700	700	5868	5302	31,3	184,9	169,4		
		1050	8390	7577	48,5	170,5	156,1		
		1400	10614	9580	66,7	156,9	143,6		
PALS00012-2P8S-30-5050	3000	700	6147	5554	31,3	193,7	177,5		
		1050	8790	7938	48,5	178,6	163,5		
		1400	11119	10036	66,7	164,4	150,4		
PALS00012-2P8S-40-5050	4000	700	6520	5891	31,3	205,4	188,3		
		1050	9322	8419	48,5	189,5	173,5		
		1400	11793	10644	66,7	174,4	159,5		
PALS00012-2P8S-50-5050	5000	700	6520	5891	31,3	205,4	188,3		
		1050	9322	8419	48,5	189,5	173,5		
		1400	11793	10644	66,7	174,4	159,5		
PALS00012-2P8S-65-5050	6500	700	6240	5638	31,3	196,6	180,2		
		1050	8923	7555	45,5	181,3	166		
		1400	11287	10188	66,7	166,9	152,7		