



### PRODUCT FEATURES

- \*Ideal For Street, High Bay, Low Bay Lighting
- \*Up to 205 lm/W LED Module Efficiency
- \*5050 Package High Performance LEDs
- \*Wide CCT Ranging from 2200K – 6500K
- \*Long Life-Time: > 100.000 Hours L70B10 @105°C
- \*Minimum Colour Tolerance: 3MacAdam (3SDCM)
- \*Compatible with Ledil Strada-2x2 and HB-2x2 Families



Product Code	CCT K	Current mA	Flux tc 25°C lm	Flux tc 85°C lm	Power tc 85°C W	Efficacy tc 25°C lm/W	Efficacy tc 85°C lm/W	Vmin. Tc 85°C	Vmax. Tc 25°C
PALS00013-2P6S-22-5050	2200	700	3842	3471	23,5	161,4	147,9	33.54	36.24
		1050	5494	4961	36,4	148,9	136,3		
		1400	6949	6273	50,1	137	125,3		
PALS00013-2P6S-27-5050	2700	700	4401	3976	23,5	184,9	169,4		
		1050	6293	5683	36,4	170,5	156,1		
		1400	7960	7185	50,1	156,9	143,6		
PALS00013-2P6S-30-5050	3000	700	4610	4166	23,5	193,7	177,5		
		1050	6592	5953	36,4	178,6	163,5		
		1400	8339	7527	50,1	164,4	150,4		
PALS00013-2P6S-40-5050	4000	700	4890	4418	23,5	205,4	188,3		
		1050	6992	6314	36,4	189,5	173,5		
		1400	8845	7983	50,1	174,4	159,5		
PALS00013-2P6S-50-5050	5000	700	4890	4418	23,5	205,4	188,3		
		1050	6992	6314	36,4	189,5	173,5		
		1400	8845	7983	50,1	174,4	159,5		
PALS00013-2P6S-65-5050	6500	700	4680	4229	23,5	196,6	180,2		
		1050	6692	6044	36,4	181,3	166		
		1400	8466	7641	50,1	166,9	152,7		