



PRODUCT FEATURES

- *Solutions For Premium Class Indoor Lighting
- *Up to 197 lm/W LED Module Efficiency
- *2835 Package High Performance LEDs
- *Wide CCT Ranging From 3000K – 6500K
- *Long Life-Time: >72.000 Hours L70B10 @85°C
- *Minimum Colour Tolerance: 3MacAdam (3SDCM)
- *2835PRO Versions are Proper For Outdoor Applications
- *Proper to LEDIL LINDA-24

Product Code	CCT K	Current mA	Flux tc 25°C lm	Flux tc 65°C lm	Power tc 65°C W	Efficacy tc 25°C lm/W	Efficacy tc 65°C lm/W	Vmin. Tc 65°C	Vmax. Tc 25°C
PALS00014-3P16S-30-2835	3000	250	2084	1944	11,4	181	171,7	45,44	46,88
		300	2478	2310	13,8	177,6	167,9		
		350	2862	2668	16,2	174,4	164,8		
PALS00014-3P16S-40-2835	4000	250	2175	2028	11,4	188,8	178,6		
		300	2585	2410	13,8	185,3	175,2		
		350	2987	2784	16,2	182	172		
PALS00014-3P16S-50-2835	5000	250	2205	2056	11,4	191,5	181		
		300	2621	2444	13,8	187,9	177,6		
		350	3028	2803	16,2	184,5	174,4		
PALS00014-3P16S-65-2835	6500	250	2175	2028	11,4	188,8	178,6		
		300	2585	2410	13,8	185,3	175,2		
		350	2987	2784	16,2	182	172		
PALS00014-3P16S-30-2835PRO	3000	250	2185	2083	11,4	189,6	183,2	45,44	47,04
		300	2602	2481	13,8	186,2	179,8		
		350	3013	2872	16,3	183	176,7		
PALS00014-3P16S-40-2835PRO	4000	250	2276	2170	11,4	197,5	190,8		
		300	2711	2584	13,8	194	187,3		
		350	3138	2992	16,3	190,6	184		
PALS00014-3P16S-50-2835PRO	5000	250	2276	2170	11,4	197,5	190,8		
		300	2711	2584	13,8	194	187,3		
		350	3138	2992	16,3	190,6	184		
PALS00014-3P16S-65-2835PRO	6500	250	2276	2170	11,4	197,5	190,8		
		300	2711	2584	13,8	194	187,3		
		350	3138	2992	16,3	190,6	184		