



### PRODUCT FEATURES

- \*Solutions For Premium Class Indoor Lighting
- \*Up to 198 lm/W LED Module Efficiency
- \*2835 Package High Performance LEDs
- \*Wide CCT Ranging From 3000K – 6500K
- \*Long Life-Time: >72.000 Hours L70B10 @85°C
- \*Minimum Colour Tolerance: 3MacAdam (3SDCM)
- \*2835PRO Versions are Proper For Outdoor Applications
- \*Proper to LEDIL LINDA-24

Product Code	CCT K	Current mA	Flux tc 25°C lm	Flux tc 65°C lm	Power tc 65°C W	Efficacy tc 25°C lm/W	Efficacy tc 65°C lm/W	Vmin. Tc 65°C	Vmax. Tc 25°C
PALS00015-9P13S-30-2835	3000	700	4757	4435	25,8	182,1	172,2	36,79	38,09
		900	6039	5631	33,5	177,6	167,9		
		1050	6977	6504	39,5	174,4	164,8		
PALS00015-9P13S-40-2835	4000	700	4964	4628	25,8	190,1	179,7		
		900	6302	5875	33,5	185,3	175,2		
		1050	7281	6787	39,5	182	172		
PALS00015-9P13S-50-2835	5000	700	5033	4693	25,8	192,7	182,2		
		900	6389	5957	33,5	187,9	177,6		
		1050	7382	6881	39,5	184,5	174,4		
PALS00015-9P13S-65-2835	6500	700	4964	4628	25,8	190,1	179,7		
		900	6302	5875	33,5	185,3	175,2		
		1050	7281	6787	39,5	182	172		
PALS00015-9P13S-30-2835PRO	3000	700	4984	4751	25,8	190,8	184,3	36,79	38,22
		900	6343	6047	33,6	186,2	179,8		
		1050	7344	7000	39,6	183	176,7		
PALS00015-9P13S-40-2835PRO	4000	700	5192	4949	25,8	198,8	192		
		900	6607	6299	33,6	194	187,3		
		1050	7650	7292	39,6	190,6	184		
PALS00015-9P13S-50-2835PRO	5000	700	5192	4949	25,8	198,8	192		
		900	6607	6299	33,6	194	187,3		
		1050	7650	7292	39,6	190,6	184		
PALS00015-9P13S-65-2835PRO	6500	700	5192	4949	25,8	198,8	192		
		900	6607	6299	33,6	194	187,3		
		1050	7650	7292	39,6	190,6	184		