



### PRODUCT FEATURES

- \*Solutions For Premium Class Indoor Lighting
- \*Up to 196 lm/W LED Module Efficiency
- \*2835 Package High Performance LEDs
- \*Wide CCT Ranging From 3000K – 6500K
- \*Long Life-Time: >72.000 Hours L70B10 @85°C
- \*Minimum Colour Tolerance: 3MacAdam (3SDCM)
- \*2835PRO Versions are Proper For Outdoor Applications
- \*Compatible with Ledil DAISY-7x1 Families (2X)



Product Code	CCT K	Current mA	Flux tc 25°C lm	Flux tc 65°C lm	Power tc 65°C W	Efficacy tc 25°C lm/W	Efficacy tc 65°C lm/W	Vmin. Tc 65°C	Vmax. Tc 25°C
PALS00017-4P14S-30-2835	3000	350	2548	2378	13,9	180,1	170,3	39,9	42,14
		500	3561	3319	20,3	172,8	163,3		
		700	4838	4508	29,1	163,8	154,7		
PALS00017-4P14S-40-2835	4000	350	2658	2479	13,9	187,9	177,7		
		500	3715	3463	20,3	180,4	170,4		
		700	5048	4704	29,1	170,9	161,4		
PALS00017-4P14S-50-2835	5000	350	2695	2513	13,9	190,6	180,2		
		500	3767	3511	20,3	182,9	172,8		
		700	5119	4769	29,1	173,3	163,7		
PALS00017-4P14S-65-2835	6500	350	2658	2479	14,1	187,9	177,7		
		500	3715	3463	20,3	180,4	170,4		
		700	5048	4704	29,1	170,9	161,4		
PALS00017-4P14S-30-2835PRO	3000	350	2672	2547	14,0	188,8	182,3	40,18	42,42
		500	3752	3577	20,4	181,4	175,2		
		700	5137	4896	29,3	172,9	166,9		
PALS00017-4P14S-40-2835PRO	4000	350	2783	2653	14,0	196,6	189,9		
		500	3908	3726	20,4	189	182,5		
		700	5351	5101	29,3	180,1	173,8		
PALS00017-4P14S-50-2835PRO	5000	350	2783	2653	14,0	196,6	189,9		
		500	3908	3726	20,4	189	182,5		
		700	5351	5101	29,3	180,1	173,8		
PALS00017-4P14S-65-2835PRO	6500	350	2783	2653	14,0	196,6	189,9		
		500	3908	3726	20,4	189	182,5		
		700	5351	5101	29,3	180,1	173,8		