



PRODUCT FEATURES

- *Ideal For Street, High Bay, Low Bay Lighting
- *Up to 218 lm/W LED Module Efficiency
- *3030 Package High Performance Osram Oslon Square LEDs
- *Wide CCT Ranging from 3000K – 6500K
- *Long Life-Time: > 100.000 Hours L70B10 @105°C
- *Minimum Colour Tolerance: 3MacAdam (3SDCM)
- *Compatible with Ledil STRADELLA-IP-28



Product Code	CCT K	Current mA	Flux tc 25°C lm	Flux tc 85°C lm	Power tc 85°C W	Efficacy tc 25°C lm/W	Efficacy tc 85°C lm/W	Vmin. Tc 85°C	Vmax. Tc 25°C
PALS00003-1P28S-30-3030	3000	350	5794,8	5466,8	25,6	218,6	213,5	73,36	81,76
		700	10832,8	10220	52,9	198,8	193,1		
		1050	14949,6	14103,4	77,5	178,4	182,0		
		1400	19499,3	18396	111,3	169,9	165,3		
PALS00003-1P28S-40-3030	4000	350	5794,8	5466,8	25,6	218,6	213,5		
		700	10832,8	10220	52,9	198,8	193,1		
		1050	14949,6	14103,4	77,5	178,4	182,0		
		1400	19499,3	18396	111,3	169,9	165,3		
PALS00003-1P28S-50-3030	5000	350	5794,8	5466,8	25,6	218,6	213,5		
		700	10832,8	10220	52,9	198,8	193,1		
		1050	14949,6	14103,4	77,5	178,4	182,0		
		1400	19499,3	18396	111,3	169,9	165,3		
PALS00003-1P28S-65-3030	6500	350	5794,8	5466,8	25,6	218,6	213,5		
		700	10832,8	10220	52,9	198,8	193,1		
		1050	14949,6	14103,4	77,5	178,4	182,0		
		1400	19499,3	18396	111,3	169,9	165,3		