



PRODUCT FEATURES

- *Ideal For Street, High Bay, Low Bay Lighting
- *Up to 223 lm/W LED Module Efficiency
- *3535 Package High Performance LEDs
- *Wide CCT Ranging from 2200K – 6500K
- *Long Life-Time: > 100.000 Hours L70B10 @105°C
- *Minimum Colour Tolerance: 3MacAdam (3SDCM)
- *Compatible with Ledil STRADELLA-IP-28



Product Code	CCT K	Current mA	Flux tc 25°C lm	Flux tc 85°C lm	Power tc 85°C W	Efficacy tc 25°C lm/W	Efficacy tc 85°C lm/W	Vmin. Tc 85°C	Vmax. Tc 25°C
PALS00004-1P28S-22-3535	2200	350	4947	4522	25,6	185,9	176,4	73.36	84,84
		700	9109	8324	53,7	163,6	155		
		1050	12695	11598	83,6	146,7	138,7		
		1400	15627	14272	114,8	131,6	124,3		
PALS00004-1P28S-27-3535	2700	350	4947	4522	25,6	185,9	176,4		
		700	9109	8324	53,7	163,6	155		
		1050	12695	11598	83,6	146,7	138,7		
		1400	15627	14272	114,8	131,6	124,3		
PALS00004-1P28S-30-3535	3000	350	5936	5426	25,6	223	211,7		
		700	10931	9989	53,7	196,3	186		
		1050	15234	13918	83,6	176	166,4		
		1400	18752	17127	114,8	157,9	149,2		
PALS00004-1P28S-40-3535	4000	350	5936	5426	25,6	223	211,7		
		700	10931	9989	53,7	196,3	186		
		1050	15234	13918	83,6	176	166,4		
		1400	18752	17127	114,8	157,9	149,2		
PALS00004-1P28S-50-3535	5000	350	5936	5426	25,6	223	211,7		
		700	10931	9989	53,7	196,3	186		
		1050	15234	13918	83,6	176	166,4		
		1400	18752	17127	114,8	157,9	149,2		
PALS00004-1P28S-65-3535	6500	350	5606	5124	25,6	210,6	199,9		
		700	10324	9434	53,7	185,4	175,6		
		1050	14388	13144	83,6	166,2	157,2		
		1400	17710	17175	114,8	149,2	140,9		