



### PRODUCT FEATURES

- \*Ideal For Street, High Bay, Low Bay Lighting
- \*Up to 177 lm/W LED Module Efficiency
- \*3030 Package High Performance LEDs
- \*Wide CCT Ranging from 3000K – 6500K
- \*Long Life-Time: >100.000 Hours L70B10 @105°C
- \*Minimum Colour Tolerance: 3MacAdam (3SDCM)
- \*Compatible with Ledil STRADELLA-IP-64 Families



Product Code	CCT K	Current mA	Flux tc 25°C lm	Flux tc 85°C lm	Power tc 85°C W	Efficacy tc 25°C lm/W	Efficacy tc 85°C lm/W	Vmin. Tc 85°C	Vmax. Tc 25°C
PALS00006-32S2P-30-3030	3000	200	6157	5540	36,8	150,7	163,5	184	199,36
		250	7481	6730	46,9	155,7	143,4		
		350	9934	8931	68,3	142,3	130,8		
PALS00006-32S2P-40-3030	4000	200	6422	5779	36,8	170,6	157,2		
		250	7803	7019	46,9	162,4	149,6		
		350	10361	9315	68,3	148,4	136,4		
PALS00006-32S2P-50-3030	5000	200	6510	5858	36,8	172,9	159,3		
		250	7910	7116	46,9	164,7	151,6		
		350	10504	9443	68,3	150,4	138,3		
PALS00006-32S2P-65-3030	6500	200	6444	5798	36,8	171,1	157,7		
		250	7829	7043	46,9	163,0	150,1		
		350	10397	9347	68,3	148,9	136,9		
PALS00006-16S4P-30-3030	3000	350	5466	4919	31,8	167,8	154,6	90,88	99,68
		500	7481	6730	46,9	155,7	143,4		
		700	9934	8931	68,3	142,3	130,8		
PALS00006-16S4P-40-3030	4000	350	5701	5131	31,8	175	161,3		
		500	7803	7019	46,9	162,4	149,6		
		700	10361	9315	68,3	148,4	136,4		
PALS00006-16S4P-50-3030	5000	350	5779	5201	31,8	177,4	163,5		
		500	7910	7116	46,9	164,7	151,6		
		700	10504	9443	68,3	150,4	138,3		
PALS00006-16S4P-65-3030	6500	350	5721	5148	31,8	175,6	161,8		
		500	7829	7043	46,9	163,0	150,1		
		700	10397	9347	68,3	148,9	136,9		