



PRODUCT FEATURES

- *Ideal For Street, High Bay, Low Bay Lighting
- *Up to 223 lm/W LED Module Efficiency
- *3535 Package High Performance LEDs
- *Wide CCT Ranging from 2200K – 6500K
- *Long Life-Time: > 100.000 Hours L70B10 @105°C
- *Minimum Colour Tolerance: 3MacAdam (3SDCM)
- *Compatible with Ledil Strada-2x2 and HB-2x2 Families



Product Code	CCT K	Current mA	Flux tc 25°C lm	Flux tc 85°C lm	Power tc 85°C W	Efficacy tc 25°C lm/W	Efficacy tc 85°C lm/W	Vmin. Tc 85°C	Vmax. Tc 25°C
PALS00009-1P8S-22-3535	2200	350	1413	1292	7,3	185,9	176,4	20.96	24.24
		700	2603	2378	15,3	163,6	155		
		1050	3627	3314	23,9	146,7	138,7		
		1400	4465	4078	32,8	131,6	124,3		
PALS00009-1P8S-27-3535	2700	350	1413	1292	7,3	185,9	176,4		
		700	2603	2378	15,3	163,6	155		
		1050	3627	3314	23,9	146,7	138,7		
		1400	4465	3289	23,6	131,6	139,1		
PALS00009-1P8S-30-3535	3000	350	1696	1550	7,3	223	211,7		
		700	3123	2854	15,3	196,3	186		
		1050	4353	3976	23,9	176	166,4		
		1400	5358	4893	32,8	157,9	149,2		
PALS00009-1P8S-40-3535	4000	350	1696	1550	7,3	223	211,7		
		700	3123	2854	15,3	196,3	186		
		1050	4353	3976	23,9	176	166,4		
		1400	5358	4893	32,8	157,9	149,2		
PALS00009-1P8S-50-3535	5000	350	1696	1550	7,3	223	211,7		
		700	3123	2854	15,3	196,3	186		
		1050	4353	3976	23,9	176	166,4		
		1400	5358	4893	32,8	157,9	149,2		
PALS00009-1P8S-65-3535	6500	350	1602	1464	7,3	210,6	199,9		
		700	2950	2695	15,3	185,4	175,6		
		1050	4111	3756	23,9	166,2	157,2		
		1400	5060	4621	32,8	149,2	140,9		