



PRODUCT FEATURES

- *Solutions For Premium Class Indoor Lighting
- *Up to 194 lm/W LED Module Efficiency
- *2835 Package High Performance LEDs
- *Wide CCT Ranging From 3000K – 6500K
- *Long Life-Time: >72.000 Hours L70B10 @85°C
- *Minimum Colour Tolerance: 3MacAdam (3SDCM)
- *2835PRO Versions are Proper For Outdoor Applications
- *Compatible with Ledil DAISY-7x1 Families



Product Code	CCT K	Current mA	Flux tc 25°C lm	Flux tc 65°C lm	Power tc 65°C W	Efficacy tc 25°C lm/W	Efficacy tc 65°C lm/W	Vmin. Tc 65°C	Vmax. Tc 25°C
PALS00016-2P14S-30-2835	3000	200	1445	1347	8,0	177,6	167,9	40,18	42,14
		250	1780	1660	10,2	172,8	163,3		
		350	2419	2254	14,6	163,8	154,7		
PALS00016-2P14S-40-2835	4000	200	1508	1406	8,0	185,3	175,2		
		250	1858	1732	10,2	180,4	170,4		
		350	2524	2352	14,6	170,9	161,4		
PALS00016-2P14S-50-2835	5000	200	1529	1426	8,0	187,9	177,6		
		250	1884	1756	10,2	182,9	172,8		
		350	2559	2385	14,6	173,3	163,7		
PALS00016-2P14S-65-2835	6500	200	1508	1406	8,0	185,3	175,2		
		250	1858	1732	10,2	180,4	170,4		
		350	2524	2352	14,6	170,9	161,4		
PALS00016-2P14S-30-2835PRO	3000	200	1518	1447	8,0	186,2	179,8	40,18	42,42
		250	1876	1788	10,2	181,4	175,2		
		350	2568	2448	14,7	172,9	166,9		
PALS00016-2P14S-40-2835PRO	4000	200	1581	1507	8,0	194	187,3		
		250	1954	1863	10,2	189	182,5		
		350	2676	2550	14,7	180,1	173,8		
PALS00016-2P14S-50-2835PRO	5000	200	1581	1507	8,0	194	187,3		
		250	1954	1863	10,2	189	182,5		
		350	2676	2550	14,7	180,1	173,8		
PALS00016-2P14S-65-2835PRO	6500	200	1581	1507	8,0	194	187,3		
		250	1954	1863	10,2	189	182,5		
		350	2676	2550	14,7	180,1	173,8		