



PRODUCT FEATURES

- *Solutions For Premium Class Indoor Lighting
- *Up to 194 lm/W LED Module Efficiency
- *2835 Package High Performance LEDs
- *Wide CCT Ranging From 3000K – 6500K
- *Long Life-Time: >72.000 Hours L70B10 @85°C
- *Minimum Colour Tolerance: 3MacAdam (3SDCM)
- *2835PRO Versions are Proper For Outdoor Applications
- *Compatible with Ledil DAISY-2x2 Families



Product Code	CCT K	Current mA	Flux tc 25°C lm	Flux tc 65°C lm	Power tc 65°C W	Efficacy tc 25°C lm/W	Efficacy tc 65°C lm/W	Vmin. Tc 65°C	Vmax. Tc 25°C
PALS00018-2P8S-30-2835	3000	200	826	770	4,6	177,6	167,9	22,96	24,08
		250	1017	948	5,8	172,8	163,3		
		350	1382	1288	8,3	163,8	154,7		
PALS00018-2P8S-40-2835	4000	200	862	803	4,6	185,3	175,2		
		250	1062	990	5,8	180,4	170,4		
		350	1442	1344	8,3	170,9	161,4		
PALS00018-2P8S-50-2835	5000	200	874	815	4,6	187,9	177,6		
		250	1076	1003	5,8	182,9	172,8		
		350	1462	1363	8,3	173,3	163,7		
PALS00018-2P8S-65-2835	6500	200	862	803	4,6	185,3	175,2		
		250	1062	990	5,8	180,4	170,4		
		350	1442	1344	8,3	170,9	161,4		
PALS00018-2P8S-30-2835PRO	3000	200	867	827	4,6	186,2	179,8	22,96	24,24
		250	1072	1022	5,8	181,4	175,2		
		350	1468	1399	8,4	172,9	166,9		
PALS00018-2P8S-40-2835PRO	4000	200	904	861	4,6	194	187,3		
		250	1117	1064	5,8	189	182,5		
		350	1529	1457	8,4	180,1	173,8		
PALS00018-2P8S-50-2835PRO	5000	200	904	861	4,6	194	187,3		
		250	1117	1064	5,8	189	182,5		
		350	1529	1457	8,4	180,1	173,8		
PALS00018-2P8S-65-2835PRO	6500	200	904	861	4,6	194	187,3		
		250	1117	1064	5,8	189	182,5		
		350	1529	1457	8,4	180,1	173,8		